

# Celebrity<sup>®</sup> DELUXE

The Celebrity<sup>®</sup> Deluxe delivers superb performance and ease of use with sleek, sporty styling for an overall package that impresses with elegant simplicity. Loaded with standard features like an infinite adjustable tiller, manual recline, and dual-bulb lower light for pathway illumination, the Celebrity Deluxe is equipped to excite.



Celebrity<sup>®</sup> Deluxe 4-wheel  
Shown in Red

**Pride**<sup>®</sup>  
Mobility Products Ltd.

32 Wedgwood Road  
Bicester, Oxfordshire, OX26 4UL  
Tel: 01869 324 600  
Fax: 01869 323 070



[www.pridemobility.com](http://www.pridemobility.com)

# Celebrity<sup>®</sup> DELUXE

## Specifications:

WEIGHT CAPACITY:	159kg (25 STONE)
MAXIMUM SPEED:	Up to 9.5 km/h (6.25 mph)
GROUND CLEARANCE:	9 cm (3.5")
TURNING RADIUS:	150 cm (59")
LENGTH:	119 cm (46.75")
WIDTH:	61 cm (24")
FRONT TYRES:	9 cm x 25 cm (3.5" x 10")
REAR TYRES:	10 cm x 25 cm (4" x 10")
ANTI-TIPS:	Rear
STANDARD SEAT:	Deluxe seat with headrest
SUSPENSION:	Front and rear
BATTERY CHARGER:	Off-board
PER-CHARGE RANGE:**	Up to 45 km (28 miles)
BATTERIES:	2 x 30 amp standard
BATTERY WEIGHT:	(2) 11 kg (24.5 lbs.) each
TOTAL WEIGHT w/o	
BATTERY PACKS:	68.5 kg (151 lbs.)
HEAVIEST PIECE	
WHEN DISASSEMBLED:	30 kg (65.5 lbs)

## Features:

- State-of-the-art rear suspension
- Maximum speed up to 9.5 km/h (6.25 mph)
- Maximum weight capacity of 159 kg (25 STONE)
- Ultra-simple, auto-latching lock-up for quick disassembly/reassembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- Tight turning radius of 150 cm (59")
- Includes standard angle-adjustable dual bulb kerb light
- Front frame-mounted seat post for optimal stability
- Standard removable battery charger storage bag
- High visibility reflectors
- Microprocessor based controller
- Tiller rotation lock permits tiller to be used as handle during transport

## Colours:



Red

## Options:

- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Walker holder
- Upgrade to 40 amp batteries

\*The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice.\*

\*\*Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement.\*