

# Celebrity<sup>®</sup> XL8

The all-new Celebrity<sup>®</sup> XL8 takes scooters to a new level of refinement convenience and performance. With a standard delta tiller with wraparound handles, independent console angle adjustment, deluxe high-back reclining captain's seat, full directional light package and one-handed tiller angle adjustment, the Celebrity XL8 is our most feature filled scooter in its class.



Celebrity<sup>®</sup> XL8  
Shown in Red

**Pride**<sup>®</sup>  
Mobility Products Ltd.

32 Wedgwood Road  
Bicester, Oxfordshire, OX26 4UL  
Tel: 01869 324 600  
Fax: 01869 323 070



[www.pridemobility.com](http://www.pridemobility.com)

# Celebrity<sup>®</sup> XL8

## Specifications:

<b>WEIGHT CAPACITY:</b>	159kg (25 STONE)
<b>MAXIMUM SPEED:</b>	Up to 13 km/h (8 mph)
<b>GROUND CLEARANCE:</b>	11 cm (4.25")
<b>TURNING RADIUS:</b>	168.27 cm (66.25")
<b>LENGTH:</b>	130.17 cm (51.25")
<b>WIDTH:</b>	64 cm (25.25")
<b>FRONT TYRES:</b>	10 cm x 33 cm (4" x 13")
<b>REAR TYRES:</b>	10 cm x 33 cm (4" x 13")
<b>ANTI-TIPS:</b>	Rear
<b>STANDARD SEAT:</b>	Deluxe reclining high-back
<b>SUSPENSION:</b>	Front and rear
<b>BATTERY CHARGER:</b>	Off-board
<b>PER-CHARGE RANGE:**</b>	Up to 48 km (30 miles)
<b>BATTERIES:</b>	2 x 30 amp (standard) or 2 x 40 amp (optional)
<b>BATTERY WEIGHT:</b>	30 amp: 11 kg (24.5 lbs.) each 40 amp: 14 kg (31 lbs.) each
<b>TOTAL WEIGHT w/o</b>	
<b>BATTERY PACKS:</b>	91 kg (200 lbs.)
<b>HEAVIEST PIECE</b>	
<b>WHEN DISASSEMBLED:</b>	37.65 kg (83 lbs)

## Colours:



Red

## Features:

- State-of-the-art suspension (front and rear)
- Maximum speed up to 13 km/h (8 mph)
- Maximum weight capacity of 159 kg (25 STONE)
- Ultra-simple, auto-latching lock-up for quick disassembly/reassembly
- Easily accessible tie down points (for transport of unoccupied scooter)
- Front basket standard
- Tight turning radius of 168.27 cm (66.25")
- Includes standard angle-adjustable dual bulb kerb light
- Front frame-mounted seat post for optimal stability
- Standard removable battery charger storage bag
- High visibility reflectors
- Microprocessor based controller
- Tiller rotation lock permits tiller to be used as handle during transport

## Options:

- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Walker holder
- Upgrade to 40 amp batteries

\*"The information contained herein is correct at the time of publication; due to the manufacturer's commitment to constant improvement and development, they reserve the right to alter specifications without prior notice."

\*\*"Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement."